

On page 7, line 6, please insert after "CVD of Cu" – as shown in Figure 11 --.

On page 8, line 15, please delete "58" and insert – 68 – therefor.

IN THE CLAIMS:

Please amend the claims as follows:

- B -
2nd
D1
1. (Amended) A method of filling a feature formed in [hole through] a dielectric layer [in an integrated circuit], comprising:
 - a) depositing a generally conformal first barrier layer in the feature [hole];
 - b) removing the first barrier layer formed on the bottom of the feature [hole];
 - c) sputter depositing a second barrier layer under conditions of a high density plasma, wherein the second barrier layer comprises a material selected from a group consisting of Ta, TaN, TaSiN, TiSiN, and combinations thereof; and
 - d) depositing a metal layer in the feature [hole], wherein the metal layer comprises copper.
 2. (Amended) The method of claim 1, wherein the first barrier layer is deposited using chemical vapor deposition techniques.
 3. (Amended) The method of claim 2, wherein the first barrier layer is comprised of Si_xN_y .
 4. (Amended) The method of claim 3, wherein [a portion of] the first barrier layer formed on the bottom of the feature [hole] is removed using etching techniques.
 5. (Amended) The method of claim 4, wherein the metal layer deposited in the feature [hole] is copper.

6. (Amended) The method of claim 5, wherein the metal layer is deposited using chemical vapor deposition techniques.

7. (Amended) The method of claim 5, wherein the metal layer is deposited using physical vapor deposition techniques.

8. (Amended) The method of claim 1, wherein the first barrier layer comprises Si_xN_y .

9. (Canceled) The method of claim 8 wherein the second barrier layer comprises a material selected from the group consisting of Ta, TaN, TaSiN, TiSiN and combinations thereof.

10. (Canceled) The method of claim 9 wherein the metal layer sputter deposited in the hole is copper.

11. (Amended) The method of claim 1 [10], wherein the second barrier layer is sputter deposited under the conditions of a high density plasma.

12. (Amended) The method of claim 11, wherein the metal layer is sputter deposited under the conditions of a high density plasma.

13. (Amended) The method of claim 12, wherein the metal layer is heated to a temperature of between about room temperature and about 500°C and then subjected to a pressurized environment.

14. (Amended) The method of claim 13, wherein the pressurized environment is in the range of about 1000 psi to about 100,000 psi.

15. (Amended) A method of [filling] forming a feature [hole through] in a dielectric layer [in an integrated circuit], comprising:

a) depositing a first barrier layer over a blanket dielectric layer;

- sub
D2
D3
D4
D5
D6
D7
D8
D9
D10
D11
D12
D13
D14
D15
D16
D17
D18
D19
D20
D21
D22
D23
D24
D25
D26
D27
D28
D29
D30
D31
D32
D33
D34
D35
D36
D37
D38
D39
D40
D41
D42
D43
D44
D45
D46
D47
D48
D49
D50
D51
D52
D53
D54
D55
D56
D57
D58
D59
D60
D61
D62
D63
D64
D65
D66
D67
D68
D69
D70
D71
D72
D73
D74
D75
D76
D77
D78
D79
D80
D81
D82
D83
D84
D85
D86
D87
D88
D89
D90
D91
D92
D93
D94
D95
D96
D97
D98
D99
D100
- b) forming a feature [hole] through the barrier layer and the dielectric layer to expose an underlayer;
- c) depositing a second generally conformal barrier layer in the feature [hole];
- d) removing the barrier layer formed at the bottom of the feature [hole];
- e) selectively depositing a metal layer on the underlayer exposed in the feature [hole].

16. (Amended) The method of claim 15, wherein the first barrier layer and the second barrier layer[s] are comprised of Si_xN_y .

17. (Amended) The method of claim 16, wherein the first barrier layer and the second barrier layer[s] are formed using chemical vapor deposition techniques.

18. (Amended) The method of claim 17, wherein the barrier layer formed on the bottom of the feature [hole] is removed by sputter etching techniques.

19. (Canceled) An integrated processing tool, comprising:

- a central transfer chamber having a robot assembly disposed at least partially therein for moving substrates;
- a chemical vapor deposition chamber for depositing Si_xN_y ;
- a high density plasma physical vapor deposition chamber connected to the transfer chamber having a target comprising tantalum;
- an etch chamber capable of achieving a high density plasma; and
- a high density plasma physical vapor deposition chamber connected to the transfer chamber having a target comprising copper.

20. (Amended) The method of claim 5, wherein the metal layer is deposited by first depositing a wetting layer using chemical vapor deposition techniques and then filling the feature [hole] using physical vapor deposition techniques.